



# WEST VALLEY REGIONAL FIRE TRAINING CONSORTIUM



## ENGINE COMPANY

### STANDARD TRAINING EVOLUTION

#### EVOLUTION DESCRIPTION

103

2 1/2" HOSELINE FOR FIRE ATTACK / EXPOSURES

#### EQUIPMENT PERFORMANCE STANDARD

(1) Engine Co.  
Water Supply  
Simulated Target  
Stopwatch

3 FF COMPANY

4 FF COMPANY

0:00

0:00

#### PROCEDURE

- TIME STARTS**
- ENGINE SPOTS AT HYDRANT
  - ENGINE SECURES SUPPLY
  - DEPLOY 200' x 2 1/2" HOSELINE FOR FIRE ATTACK / EXPOSURE PROTECTION ESTABLISH HOSE STREAM (250 GPM) TO TARGET AREA
  - REPOSITION LINE (ADVANCE 50 FT.) AND RE-ESTABLISH FLOW

- TIME STOPS** HOSE LINE IN OPERATION & OBJECTIVES COMPLETE:
- HOSE ADVANCED TO TARGET, ADEQUATE FLOW ESTABLISHED (250 GPM)
  - WATER SUPPLY IS SECURED
  - RELIEF VALVE SET ACCORDING TO DEPARTMENT SOG

#### DIAGRAM



#### REFERENCE

NFPA 1410 : STANDARD ON TRAINING FOR INITIAL EMERGENCY SCENE OPERATIONS  
DEPARTMENT / REGIONAL SOGs

A.6.1.1(a)  
#